

# Gfp 400 Series Top Heat Laminators

Increase profits with a variety of popular Pressure-Sensitive applications.



The **Gfp 400 Series** laminators are money makers. Easy to operate, they're a favorite with operators that prefer a simple time-saving set-up and variable roller gap adjustment. Ruggedly built for applications that require overlamination, mounting or the pre-coating of boards, the 400 Series laminators are **available in 55" and 63" widths**. Thanks to oversized rollers and 1 inch roller gap, you'll be making money in no time.

- ✓ Roller diameter 4.5"
- ✓ Speed and temperature controls
- ✓ Reverse switch
- ✓ Foot pedal
- ✓ 2 unwind film shafts
- ✓ 1 aluminum take-up mandrel
- ✓ Swing up feed table
- ✓ CE Certified

- ✓ Variable roller gap to 1"
- ✓ Photoelectric eye
- ✓ Front unwind basket
- ✓ In feed pressure roller
- ✓ 3" core film chucks
- ✓ Dual tension control
- ✓ Machine stand with casters
- ✓ 36" table height output



*The Profitable Source for Finishing Products*

# Choose the 400 Series Professional Top Heat Laminators for Overlamination Mounting Board pre-coating



Simple, easy to use speed and temperature controls



Motorized rear rewind for roll-to-roll applications

## We have supplies!

We carry a full line of wide format finishing supplies in a variety of materials, weights, and finishes.



### Applications

Signs  
Banners  
Trade show displays  
Point-of-purchase displays  
Dry-erase boards  
Floor graphics  
Graphic mounting  
Photo mounting  
Window graphics  
Vehicle graphics

### Specifications

|                         | 455TH                 | 463TH                 |
|-------------------------|-----------------------|-----------------------|
| Laminating Width        | 55"                   | 63"                   |
| Roller diameter         | 4.5"                  | 4.5"                  |
| Roller gap              | 1"                    | 1"                    |
| Rear rewind             | Optional              | Optional              |
| Max temperature         | 140° F                | 140° F                |
| Laminating speed        | 0-11.5 ft/min         | 0-13 ft/min           |
| Pressure adjustment     | Hand wheel            | Hand wheel            |
| Heat method             | Quartz tube           | Quartz tube           |
| Max. Roll diameter      | 10" OD                | 10" OD                |
| Power supply            | 110v                  | 110v                  |
| Power consumption       | 1100 W                | 1400 W                |
| Net weight w/ stand     | 388 lbs               | 427 lbs               |
| Dimensions              | 72" x 23.4" x 46.5"   | 82" x 23.4" x 46.5"   |
| Shipping weight machine | 419 lbs               | 445 lbs               |
| Shipping weight stand   | 82 lbs                | 97 lbs                |
| Shipping dim. machine   | 79.5" x 27.6" x 25.5" | 87.4" x 27.6" x 25.5" |
| Shipping dim. stand     | 64.8" x 26" x 6.3"    | 72.6" x 26" x 6.3"    |



The Profitable Source for Finishing Products