

# Maximum Productivity

## 563TH MaxPro

Top Heat Laminator



### The fastest way to profitability for Pressure-Sensitive applications.

What's the best way to make your production even better? Shorten film loading time? Make fewer film changes? Increase throughput speed? Increase bi-directional flexibility? Yes. And that's exactly what we did to create our most productive 63" laminator. The Gfp 563TH MAXPRO saves time, effort and money on your applications that require overlamination, mounting or the pre-coating of boards.

#### Applications

*Signs*  
*Banners*  
*Trade show displays*  
*Point-of-purchase displays*  
*Dry-erase boards*  
*Floor graphics*  
*Graphic mounting*  
*Photo mounting*  
*Window graphics*  
*Vehicle graphics*

- ✓ **Easier loading** with Front and Rear Swing-Out Film Shafts
- ✓ **Fewer supply changes** with new 300' roll capacity
- ✓ **50% faster throughput** of 20 ft/min
- ✓ **Quicker application changes** thanks to Bi-directional flexibility



*The Profitable Source for Finishing Products*

## Overlamination Mounting Board pre-coating

The 563THMAXPRO will boost productivity by over 50%.




Simple speed and temperature controls



Motorized rear rewind for roll-to-roll applications



Fewer film changes with 300' rolls.



Swing-out Film Shafts on both sides make loading easy for operators.

### Specifications

	<b>563THMAXPRO</b>
Laminating Width	63"
Roller diameter	4.5"
Roller gap	1"
Rear rewind	Optional
Max temperature	140° F
Laminating speed	0-20 ft/min
Pressure adjustment	Hand wheel
Heat method	Quartz tube
Max. roll diameter	10" OD
Power supply	110v
Power consumption	1400 W
Net weight w/ stand	502 lbs
Dimensions	82" x 28.5" x 50"
Machine Shipping	507 lbs; 89.4" x 33.1" x 29.2"
Stand Shipping	143 lbs; 75" x 33" x 5.8"

- ✓ Roller diameter 4.5"
- ✓ Foot pedal
- ✓ 2 Swing-out film shafts
- ✓ Swing up feed table
- ✓ Variable roller gap to 1"
- ✓ Photoelectric eye for safety
- ✓ 3" core film chucks
- ✓ Dual tension control
- ✓ Machine stand with casters
- ✓ 36" table height output
- ✓ CE Certified



*The Profitable Source for Finishing Products*